

```

1 // foj/8/terminal/Terminal.java
2 // (and terminal/Terminal.java)
3 //
4 // Copyright 2003 Bill Campbell and Ethan Bolker
5
6 import java.io.*;
7
8 /**
9  * Terminal provides a user-friendly interface to the standard System
10 * input and output streams (in, out, and err).
11 * <p>
12 * A Terminal is an object. In general, one is expected to instantiate
13 * just one Terminal. Although one might instantiate several, all will
14 * share the same System streams.
15 * <p>
16 * A Terminal may either explicitly echo input, or not. Echoing input
17 * is useful, for example, when testing with I/O redirection.
18 * <p>
19 * Inspired by Cay Horstmann's Console Class.
20 */
21
22 public class Terminal
23 {
24     private boolean echo = false;
25     private static BufferedReader in =
26         new BufferedReader(new FileReader(FileDescriptor.in));
27
28
29     // Print a prompt to the console without a newline.
30
31     private void printPrompt( String prompt )
32     {
33         print( prompt );
34         System.out.flush();
35     }
36
37     /**
38      * Construct a Terminal that doesn't echo input.
39      */
40
41     public Terminal()
42     {
43         this( false );
44     }
45
46     /**
47      * Construct a Terminal.
48      *
49      * @param echo whether or not input should be echoed.
50      */
51
52     public Terminal( boolean echo )
53     {
54         this.echo = echo;
55     }
56

```

```

57
58     /**
59      * Read a line (terminated by a newline) from the Terminal.
60      * @param prompt output string to prompt for input.
61      * @return the string (without the newline character),
62      *         * null if eof.
63      */
64
65     public String readline( String prompt )
66     {
67         printPrompt(prompt);
68         try {
69             String line = in.readLine();
70             if (echo) {
71                 println(line);
72             }
73             return line;
74         }
75         catch (IOException e) {
76             return null;
77         }
78     }
79
80     /**
81      * Read a line (terminated by a newline) from the Terminal.
82      *
83      * @return the string (without the newline character).
84      */
85
86     public String readline()
87     {
88         return readline( "" );
89     }
90
91     // Read a line from the Terminal. An end of file,
92     // indicated by a null, raises a runtime exception.
93     // Used only internally.
94
95     private String readNonNullLine()
96     {
97         return readNonNullLine( "" );
98     }
99
100    // Read a line from the Terminal. An end of file,
101    // indicated by a null, raises a runtime exception.
102    // Used only internally.
103
104    private String readNonNullLine( String prompt )
105    {
106        String line = readline( prompt );
107        if (line == null) {
108            throw new RuntimeException( "End of file encountered. " );
109        }
110        return line;
111    }
112

```

```

113  /**
114  * Read a word from the Terminal.
115  * If an empty line is entered, try again.
116  * Words are terminated by whitespace.
117  * Leading whitespace is trimmed; the rest of the line
118  * is disposed of.
119  *
120  * @param prompt output string to prompt for input.
121  * @return the word read.
122  */
123  public String readWord( String prompt )
124  {
125      String line = readNonNullLine( prompt );
126      if (line.length() == 0) {
127          println( "Empty line. Please try again." );
128          return readWord( "" );
129      }
130      line = line.trim();
131      for ( int i = 0; i < line.length(); i++ ) {
132          if ( Character.isWhitespace( line.charAt(i) ) ) {
133              return line.substring( 0, i );
134          }
135      }
136      return line;
137  }
138  /**
139  * Read a word from the Terminal.
140  * If an empty line is entered, try again.
141  * Words are terminated by whitespace.
142  * Leading whitespace is trimmed; the rest of the line
143  * is disposed of.
144  *
145  * @return the word read.
146  */
147  public String readWord()
148  {
149      return readWord( "" );
150  }
151  /**
152  * Read a word from the Terminal.
153  * If an empty line is entered, throw an exception.
154  * Words are terminated by whitespace.
155  * Leading whitespace is trimmed; the rest of the line
156  * is disposed of.
157  *
158  * @param prompt output string to prompt for input.
159  * @return the word read.
160  * @throws RuntimeException if it reads an empty line.
161  */
162  public String readWordOnce( String prompt )
163  {
164      String line = readNonNullLine( prompt );
165      if (line.length() == 0) {
166          println( "No character on line. Please try again." );
167          return readChar( "" );
168      }

```

```

169      return line;
170  }
171  /**
172  * Read a character from the Terminal.
173  * If an empty line is entered, throw an exception.
174  * Words are terminated by whitespace.
175  * Leading whitespace is trimmed; the rest of the line
176  * is disposed of.
177  *
178  * @param prompt output string to prompt for input.
179  * @return the character read.
180  * @throws RuntimeException if it reads an empty line.
181  */
182  public char readChar( String prompt )
183  {
184      String line = readNonNullLine( prompt );
185      if (line.length() == 0) {
186          println( "Empty line encountered." );
187          throw new RuntimeException( "Empty line encountered." );
188      }
189      line = line.trim();
190      for ( int i = 0; i < line.length(); i++ ) {
191          if ( Character.isWhitespace( line.charAt(i) ) ) {
192              return line.substring( 0, i );
193          }
194      }
195      return line.charAt(0);
196  }
197  /**
198  * Read a character from the Terminal.
199  * If an empty line is entered, throw an exception.
200  * Words are terminated by whitespace.
201  * Leading whitespace is trimmed; the rest of the line
202  * is disposed of.
203  *
204  * @param prompt output string to prompt for input.
205  * @return the character read.
206  */
207  public char readCharOnce( String prompt )
208  {
209      String line = readNonNullLine( prompt );
210      if (line.length() == 0) {
211          println( "No character on line. Please try again." );
212          return readChar( "" );
213      }
214      return line.charAt(0);
215  }
216  /**
217  * Read a character from the Terminal.
218  * If an empty line is entered, throw an exception.
219  * Words are terminated by whitespace.
220  * Leading whitespace is trimmed; the rest of the line
221  * is disposed of.
222  *
223  * @param prompt output string to prompt for input.
224  */

```

```

225  * @return the character read.
226  * @throws RuntimeException if it reads an empty line.
227  */
228  * /
229  public char readCharOnce( String prompt )
230  {
231      String line = readNonNullLine(prompt);
232      if (line.length() == 0) {
233          throw new RuntimeException("Empty line encountered.");
234      }
235      return line.charAt(0);
236  }
237  }
238  }
239  }
240  /**
241  * Read a character from the Terminal.
242  * Prompt again when an empty line is read.
243  *
244  *
245  * @return the character read.
246  */
247  public char readChar()
248  {
249      return readChar("");
250  }
251  }
252  }
253  /**
254  * Read a character from the Terminal.
255  * Throw an exception if an empty line is read.
256  *
257  * @return the character read.
258  *
259  * @throws RuntimeException if it reads an empty line.
260  */
261  public char readCharOnce()
262  {
263      return readCharOnce("");
264  }
265  }
266  }
267  }
268  /**
269  * Read "yes" or "no" from the Terminal.
270  * If an empty line or improper character is read,
271  * try again.
272  * Look only at first character and accept any case.
273  *
274  * @param prompt output string to prompt for input.
275  * @return true if yes, false if no.
276  */
277  public boolean readYesOrNo( String prompt )
278  {
279     printPrompt( prompt );
280     while ( true ) {

```

```

281     char answer = readChar( " (y or n): " );
282     if ( answer == 'y' || answer == 'Y' ) {
283         return true;
284     }
285     else if ( answer == 'n' || answer == 'N' ) {
286         return false;
287     }
288     else {
289         printPrompt( "oops!" );
290     }
291 }
292 }
293 }
294 }
295 /**
296 * Read "yes" or "no" from the Terminal.
297 * If an empty line or improper character is read,
298 * throw an exception.
299 * Look only at first character and accept any case.
300 *
301 * @param prompt output string to prompt for input.
302 * @return true if yes, false if no.
303 *
304 * @throws RuntimeException on improper input.
305 */
306 public boolean readYesOrNoOnce( String prompt )
307 {
308     printPrompt( prompt );
309     while ( true ) {
310         char answer = readCharOnce( " (y or n): " );
311         if ( answer == 'y' || answer == 'Y' ) {
312             return true;
313         }
314         else if ( answer == 'n' || answer == 'N' ) {
315             return false;
316         }
317         else {
318             throw new RuntimeException( "Must be y or n." );
319         }
320     }
321 }
322 }
323 }
324 /**
325 * Read "yes" or "no" from the Terminal.
326 * If an empty line or improper character is read,
327 * try again. No prompting is done.
328 * Look only at first character and accept any case.
329 *
330 * @return true if yes, false if no.
331 */
332 public boolean readYesOrNo()
333 {
334     while ( true ) {
335         char answer = readChar();
336         if ( answer == 'y' || answer == 'Y' ) {

```

```

337         return true;
338     }
339     else if ( answer == 'n' || answer == 'N' ) {
340         return false;
341     }
342 }
343 }
344 }
345 /**
346  * Read "yes" or "no" from the Terminal.
347  * If an empty line or improper character is read,
348  * throw an exception.
349  * Look only at first character and accept any case.
350  *
351  * @return true if yes, false if no.
352  *
353  * @throws RuntimeException on improper input.
354  */
355
356 public boolean readYesOrNoOnce()
357 {
358     char answer = readCharOnce( " (y or n): " );
359     if ( answer == 'y' || answer == 'Y' ) {
360         return true;
361     }
362     else if ( answer == 'n' || answer == 'N' ) {
363         return false;
364     }
365     else {
366         throw new RuntimeException( "Must be y or n." );
367     }
368 }
369
370 /**
371  * Read an integer, terminated by a new line, from the Terminal.
372  * If a NumberFormatException is encountered, try again.
373  *
374  * @param prompt output string to prompt for input.
375  * @return the input value as an int.
376  */
377
378 public int readInt( String prompt )
379 {
380     while( true ) {
381         try {
382             return Integer.
383                 parseInt(readNonNullLine( prompt ).trim());
384         }
385         catch (NumberFormatException e) {
386             println( "Not an integer. Please try again." );
387         }
388     }
389 }
390 /**
391  * Read an integer, terminated by a new line, from the Terminal.
392

```

```

393
394 *
395 * @param prompt output string to prompt for input.
396 * @return the input value as an int.
397 *
398 * @throws NumberFormatException for a badly formed integer.
399 */
400
401 public int readIntOnce( String prompt )
402 {
403     throws NumberFormatException
404     return Integer.parseInt(readNonNullLine( prompt ).trim());
405 }
406
407 /**
408  * Read an integer, terminated by a new line, from the Terminal.
409  * If a NumberFormatException is encountered, try again.
410  *
411  * @return the input value as an int.
412  */
413
414 public int readInt()
415 {
416     return readInt("");
417 }
418
419 /**
420  * Read an integer, terminated by a new line, from the Terminal.
421  * @return the input value as an int.
422  *
423  * @throws NumberFormatException for a badly formed integer.
424  */
425
426 public int readIntOnce()
427 {
428     throws NumberFormatException
429     return readIntOnce("");
430 }
431
432 /**
433  * Read a double-precision floating point number,
434  * terminated by a newline, from the Terminal.
435  * If a NumberFormatException is encountered, try again.
436  *
437  * @param prompt output string to prompt for input.
438  * @return the input value as a double.
439  */
440
441 public double readDouble( String prompt )
442 {
443     while( true ) {
444         try {
445             return Double.
446                 parseDouble(readNonNullLine( prompt ).trim());
447         }
448         catch (NumberFormatException e) {

```

```

449         println("Not a floating point number. Please try again.");
450     }
451 }
452 }
453 }
454 /**
455  * Read a double-precision floating point number,
456  * terminated by a newline, from the Terminal.
457  *
458  * @param prompt output string to prompt for input.
459  * @return the input value as a double.
460  *
461  * @throws NumberFormatException for a badly formed number.
462  */
463 public double readDoubleOnce( String prompt )
464     throws NumberFormatException
465 {
466     return Double.parseDouble(readNonNullLine( prompt ).trim());
467 }
468
469 /**
470  * Read a double-precision floating point number,
471  * terminated by a newline, from the Terminal.
472  *
473  * If a NumberFormatException is encountered, try again.
474  *
475  * @return the input value as a double.
476  */
477
478 public double readDouble()
479 {
480     return readDouble("");
481 }
482
483 /**
484  * Read a double-precision floating point number,
485  * terminated by a newline, from the Terminal.
486  *
487  * @return the input value as a double.
488  *
489  * @throws NumberFormatException for a badly formed number.
490  */
491
492 public double readDoubleOnce()
493     throws NumberFormatException
494 {
495     return readDouble("");
496 }
497
498 /**
499  * Print a Boolean value
500  * (<code>true</code> or <code>false</code>)
501  * to standard output (without a newline).
502  *
503  * @param b Boolean to print.
504  */

```

```

505 public void print( boolean b )
506 {
507     System.out.print( b );
508 }
509 }
510 }
511 /**
512  * Print character to standard output (without a newline).
513  *
514  * @param ch character to print.
515  *
516  * @throws NumberFormatException for a badly formed number.
517  */
518 public void print( char ch )
519 {
520     System.out.print( ch );
521 }
522
523 /**
524  * Print character array to standard output (without a newline).
525  *
526  * @param s character array to print.
527  */
528 public void print( char[] s )
529 {
530     System.out.print( s );
531 }
532
533 /**
534  * Print a double-precision floating point number to standard
535  * output (without a newline).
536  *
537  * @param val number to print.
538  */
539
540 public void print( double val )
541 {
542     System.out.print( val );
543 }
544
545 /**
546  * Print a floating point number to standard output
547  * (without a newline).
548  *
549  * @param val number to print.
550  */
551
552 public void print( float val )
553 {
554     System.out.print( val );
555 }
556
557 /**
558  * Print integer to standard output (without a newline).
559  *
560  * @param val integer to print.

```

```

561 */
562 public void print( int val )
563 {
564     System.out.println( val );
565 }
566
567 /**
568  * Print a long integer to standard output (without a newline).
569  *
570  * @param val integer to print.
571  */
572
573 public void print( long val )
574 {
575     System.out.println( val );
576 }
577
578 /**
579  * Print Object to standard output (without a newline).
580  *
581  * @param val Object to print.
582  */
583
584 public void print( Object val )
585 {
586     System.out.println( val.toString() );
587 }
588
589 /**
590  * Print string to standard output (without a newline).
591  *
592  * @param str String to print.
593  */
594
595 public void print( String str )
596 {
597     System.out.println( str );
598 }
599
600 /**
601  * Print a newline to standard output,
602  * terminating the current line.
603  */
604
605 public void println()
606 {
607     System.out.println();
608 }
609
610 /**
611  * Print a Boolean value
612  * (<code>true</code> or <code>false</code>)
613  * to standard output, followed by a newline.
614  * @param b Boolean to print.
615  */
616

```

```

617
618 public void println( boolean b )
619 {
620     System.out.println( b );
621 }
622
623 /**
624  * Print character to standard output, followed by a newline.
625  *
626  * @param ch character to print.
627  */
628
629 public void println( char ch )
630 {
631     System.out.println( ch );
632 }
633
634 /**
635  * Print a character array to standard output,
636  * followed by a newline.
637  *
638  * @param s character array to print.
639  */
640
641 public void println( char[] s )
642 {
643     System.out.println( s );
644 }
645
646 /**
647  * Print floating point number to standard output,
648  * followed by a newline.
649  *
650  * @param val number to print.
651  */
652
653 public void println( float val )
654 {
655     System.out.println( val );
656 }
657
658 /**
659  * Print a double-precision floating point number to standard
660  * output, followed by a newline.
661  *
662  * @param val number to print.
663  */
664
665 public void println( double val )
666 {
667     System.out.println( val );
668 }
669
670 /**
671  * Print integer to standard output, followed by a newline.
672  */

```

```

673      * @param val Integer to print.
674      */
675      public void println( int val )
676      {
677          System.out.println( val );
678      }
679      /**
680      * Print a long integer to standard output,
681      * followed by a newline.
682      * @param val Long integer to print.
683      */
684      public void println( long val )
685      {
686          System.out.println( val );
687      }
688      /**
689      * Print Object to standard output, followed by a newline.
690      * @param val Object to print
691      */
692      public void println( Object val )
693      {
694          System.out.println( val.toString() );
695      }
696      /**
697      * Print string to standard output, followed by a newline.
698      * @param str String to print
699      */
700      public void println( String str )
701      {
702          System.out.println( str );
703      }
704      /**
705      * Print string to standard output, followed by a newline.
706      * @param str String to print
707      */
708      public void println( String str )
709      {
710          System.out.println( str );
711      }
712      /**
713      * Print a Boolean value
714      * (<code>true</code> or <code>false</code>)
715      * to standard err (without a newline).
716      * @param b Boolean to print.
717      */
718      public void errPrint( boolean b )
719      {
720          System.err.print( b );
721      }
722      /**
723      * Print a Boolean value
724      * (<code>true</code> or <code>false</code>)
725      * to standard err (without a newline).
726      * @param b Boolean to print.
727      */
728      public void errPrint( boolean b )

```

```

729      * Print character to standard err (without a newline).
730      * @param ch character to print.
731      */
732      public void errPrint( char ch )
733      {
734          System.err.print( ch );
735      }
736      /**
737      * Print character array to standard err (without a newline).
738      * @param s character array to print.
739      */
740      public void errPrint( char[] s )
741      {
742          System.err.print( s );
743      }
744      /**
745      * Print a double-precision floating point number to standard
746      * err (without a newline).
747      * @param val number to print.
748      */
749      public void errPrint( double val )
750      {
751          System.err.print( val );
752      }
753      /**
754      * Print a floating point number to standard err
755      * (without a newline).
756      * @param val number to print.
757      */
758      public void errPrint( float val )
759      {
760          System.err.print( val );
761      }
762      /**
763      * Print a floating point number to standard err
764      * (without a newline).
765      * @param val number to print.
766      */
767      public void errPrint( float val )
768      {
769          System.err.print( val );
770      }
771      /**
772      * Print integer to standard err (without a newline).
773      * @param val integer to print.
774      */
775      public void errPrint( int val )
776      {
777          System.err.print( val );
778      }
779      /**
780      * Print integer to standard err (without a newline).
781      * @param val integer to print.
782      */
783      public void errPrint( int val )
784      {
785          System.err.print( val );
786      }

```

```

785      /**
786       * Print a long integer to standard err (without a newline).
787       *
788       * @param val integer to print.
789       */
790      public void errPrint( long val )
791      {
792          System.err.print( val );
793      }
794
795      /**
796       * Print Object to standard err (without a newline).
797       *
798       * @param val Object to print.
799       */
800      public void errPrint( Object val )
801      {
802          System.err.print( val.toString() );
803      }
804
805      /**
806       * Print string to standard err (without a newline).
807       *
808       * @param str String to print.
809       */
810      public void errPrint( String str )
811      {
812          System.err.print( str );
813      }
814
815      /**
816       * Print a newline to standard err,
817       * terminating the current line.
818       */
819      public void errPrintln()
820      {
821          System.err.println();
822      }
823
824      /**
825       * Print a Boolean value
826       * (<code>true</code> or <code>false</code>)
827       * to standard err, followed by a newline.
828       */
829      public void errPrintln( boolean b )
830      {
831          System.err.println( b );
832      }
833
834      /**
835       * Print integer to standard err, followed by a newline.
836       */
837      public void errPrintln( int val )
838      {
839          System.err.println( val );
840      }

```

```

841      /**
842       * Print character to standard err, followed by a newline.
843       *
844       * @param ch character to print.
845       */
846      public void errPrintln( char ch )
847      {
848          System.err.println( ch );
849      }
850
851      /**
852       * Print a character array to standard err,
853       * followed by a newline.
854       *
855       * @param s character array to print.
856       */
857      public void errPrintln( char[] s )
858      {
859          System.err.println( s );
860      }
861
862      /**
863       * Print floating point number to standard err,
864       * followed by a newline.
865       *
866       * @param val number to print.
867       */
868      public void errPrintln( float val )
869      {
870          System.err.println( val );
871      }
872
873      /**
874       * Print a double-precision floating point number to
875       * standard err, followed by a newline.
876       */
877      public void errPrintln( double val )
878      {
879          System.err.println( val );
880      }
881
882      /**
883       * Print integer to standard err, followed by a newline.
884       *
885       * @param val integer to print.
886       */
887      public void errPrintln( int val )
888      {
889          System.err.println( val );
890      }
891
892      /**
893       * Print integer to standard err, followed by a newline.
894       *
895       * @param val integer to print.
896       */
897      public void errPrintln( int val )
898      {
899          System.err.println( val );
900      }

```

```

897     }
898     /**
899     * Print a long integer to standard err, followed by a newline.
900     */
901     * @param val long integer to print.
902     */
903     public void errPrintln( long val )
904     {
905         System.err.println( val );
906     }
907     /**
908     * Print Object to standard err, followed by a newline.
909     */
910     * @param val Object to print
911     */
912     public void errPrintln( Object val )
913     {
914         System.err.println( val.toString() );
915     }
916     /**
917     * Print string to standard err, followed by a newline.
918     */
919     * @param str String to print
920     */
921     public void errPrintln( String str )
922     {
923         System.err.println( str );
924     }
925     /**
926     * Unit test for Terminal.
927     */
928     * @param args command line arguments:
929     * <pre>
930     * -e echo all input.
931     * </pre>
932     */
933     public static void main( String[] args )
934     {
935         Terminal t =
936             new Terminal( args.length == 1 && args[0].equals("-e") );
937         String line = t.readLine( "line:" );
938         String word = t.readWord( "word:" );
939         char c = t.readChar( "char:" );
940         boolean yn = t.readYesOrNo( "yorn:" );
941         double d = t.readDouble( "double:" );
942         int i = t.readInt( "int:" );
943     }
944
945
946
947
948
949
950
951
952

```

```

953         t.print( " line:[ ]? "); t.print( line ); t.print( " ]");
954         t.print( " line:[ ]? "); t.println( line ); t.print( " ]");
955         t.print( " word:[ ]? "); t.print( word ); t.print( " ]");
956         t.print( " word:[ ]? "); t.println( word ); t.print( " ]");
957         t.print( " char:[ ]? "); t.print( c ); t.print( " ]");
958         t.print( " char:[ ]? "); t.println( c ); t.print( " ]");
959         t.print( " yorn:[ ]? "); t.print( yn ); t.print( " ]");
960         t.print( " yorn:[ ]? "); t.println( yn ); t.print( " ]");
961         t.print( " doub:[ ]? "); t.print( d ); t.print( " ]");
962         t.print( " doub:[ ]? "); t.println( d ); t.print( " ]");
963         t.print( " int:[ ]? "); t.print( i ); t.print( " ]");
964         t.print( " int:[ ]? "); t.println( i ); t.print( " ]");
965         t.print( " line:[ ]? "); t.println( line ); t.print( " ]");
966         t.print( " line:[ ]? "); t.println( line ); t.print( " ]");
967         t.print( " word:[ ]? "); t.println( word ); t.print( " ]");
968         t.print( " word:[ ]? "); t.println( word ); t.print( " ]");
969         t.print( " char:[ ]? "); t.println( c ); t.print( " ]");
970         t.print( " char:[ ]? "); t.println( c ); t.print( " ]");
971         t.print( " yorn:[ ]? "); t.println( yn ); t.print( " ]");
972         t.print( " yorn:[ ]? "); t.println( yn ); t.print( " ]");
973         t.print( " doub:[ ]? "); t.println( d ); t.print( " ]");
974         t.print( " doub:[ ]? "); t.println( d ); t.print( " ]");
975         t.print( " int:[ ]? "); t.println( i ); t.print( " ]");
976         t.print( " int:[ ]? "); t.println( i ); t.print( " ]");
977         t.print( " ");
978         t.print( " ");
979         t.print( " ");
980         t.print( " ");
981         t.print( " ");
982         t.print( " ");
983         t.print( " ");
984         t.print( " ");
985         t.print( " ");
986         t.print( " ");
987         t.print( " ");
988         t.print( " ");
989         t.print( " ");
990     }

```