```
// joi/4/bank/Bank.java
//
//
// Copyright 2003 Bill Campbell and Ethan Bolker

// Lines marked "///" flag places where changes will be needed.

/// import java.util.??

/**
 * A Bank object simulates the behavior of a simple bank/ATM.
 * It contains a Terminal object and a collection of
 * BankAccount objects.
 *
 * Its public method visit opens the this Bank for business,
 * prompting the customer for input.
 *
 * To create a Bank and open it for business issue the command
 * <code>java Bank</code>.
 *
 * @see BankAccount
 * @version 4
 */

public class Bank
{
    private String bankName;           // the name of this Bank
    private Terminal atm;              // for talking with the customer
    private int balance = 0;           // total cash on hand
    private int transactionCount = 0;  // number of Bank transactions don

    private BankAccount[] accountList; /// collection of BankAccounts
    /// omit next line when accountList is dynamic
    private final static int NUM_ACCOUNTS = 3;

    // what the banker can ask of the bank

    private static final String BANKER_COMMANDS =
    "Banker commands: " +
        "exit, open, customer, report, help.";

    // what the customer can ask of the bank

    private static final String CUSTOMER_TRANSACTIONS =
    "    Customer transactions: " +
        "deposit, withdraw, transfer, balance, quit, help.";

    /**
     * Construct a Bank with the given name and Terminal.
     *
     * @param bankName the name for this Bank.
     * @param atm  this Bank's Terminal.
     */

    public Bank( String bankName, Terminal atm )
    {
```



```
        this.atm      = atm;
        this.bankName = bankName;
        // initialize collection:
        accountList   = new BankAccount[NUM_ACCOUNTS]; ///

        /// When accountList is an array, fill it here.
        /// When it's an ArrayList or a TreeMap, delete these lines.
        /// Bank starts with no accounts, banker creates them with
        /// the openNewAccount method.
        accountList[0] = new BankAccount(  0, this);
        accountList[1] = new BankAccount(100, this);
        accountList[2] = new BankAccount(200, this);
    }

    /**
     * Simulates interaction with a Bank.
     * Presents the user with an interactive loop, prompting for
     * banker transactions and in case of the banker transaction
     * "customer", an account id and further customer
     * transactions.
     */

    public void visit()
    {
        instructUser();

        String command;
        while (!(command =
                 atm.readWord("banker command: ")).equals("exit")) {

            if (command.startsWith("h")) {
                help( BANKER_COMMANDS );
            }
            else if (command.startsWith("o")) {
                openNewAccount();
            }
            else if (command.startsWith("r")) {
                report();
            }
            else if (command.startsWith( "c" ) ) {
                BankAccount acct = whichAccount();
                if ( acct != null )
                    processTransactionsForAccount( acct );
            }
            else {
                // Unrecognized Request
                atm.println( "unknown command: " + command );
            }
        }
        report();
        atm.println( "Goodbye from " + bankName );
    }


    // Open a new bank account,
    // prompting the user for information.
```

```
113
114     private void openNewAccount()
115     {
116         /// when accountList is a dynamic collection
117         /// remove the next two lines, uncomment and complete
118         /// the code between /* and */
119         atm.println(bankName + " is accepting no new customers\n");
120         return;
121
122         /*
123         // prompt for initial deposit
124         int startup = atm.readInt( "Initial deposit: " );
125
126         // create newAccount
127         BankAccount newAccount = new BankAccount( startup, this );
128
129         //  and add it to accountList
130         ???
131
132         // inform user
133         atm.println( "opened new account " + ??? /// name or number
134                         + " with $" + newAccount.getBalance());
135         */
136     }
137
138     // Prompt the customer for transaction to process.
139     // Then send an appropriate message to the account.
140
141     private void processTransactionsForAccount( BankAccount acct )
142     {
143         help( CUSTOMER_TRANSACTIONS );
144
145         String transaction;
146         while (!(transaction =
147                  atm.readWord("    transaction: ")).equals("quit")) {
148
149             if ( transaction.startsWith( "h" ) ) {
150                 help( CUSTOMER_TRANSACTIONS );
151             }
152             else if ( transaction.startsWith( "d" ) ) {
153                 int amount = atm.readInt( "    amount:" );
154                 atm.println("    deposited " + acct.deposit( amount ));
155             }
156             else if ( transaction.startsWith( "w" ) ) {
157                 int amount = atm.readInt( "    amount:" );
158                 atm.println("    withdrew " + acct.withdraw( amount ));
159             }
160             else if (transaction.startsWith("t")) {
161                 atm.print( "    to ");
162                 BankAccount toacct = whichAccount();
163                 if (toacct != null) {
164                     int amount = atm.readInt("    amount to transfer: ");
165                     atm.println("    transfered " +
166                                 toacct.deposit(acct.withdraw(amount)));
167                 }
168             }
```



```
169             else if (transaction.startsWith("b")) {
170                 atm.println("    current balance " +
171                             acct.requestBalance());
172             }
173             else {
174                 atm.println("    sorry, unknown transaction" );
175             }
176         }
177         atm.println();
178     }
179
180     // Prompt for an account name (or number), look it up
181     // in the account list. If it's there, return it;
182     // otherwise report an error and return null.
183
184     private BankAccount whichAccount()
185     {
186         /// prompt for account name or account number
187         /// (whichever is appropriate)
188         int accountNumber = atm.readInt("account number: ");
189
190         /// look up account in accountList
191         /// if it's there, return it
192         /// else the following two lines should execute
193         if ( accountNumber >= 0 && accountNumber < NUM_ACCOUNTS ) {
194             return accountList[accountNumber];
195         }
196         else {
197             atm.println("not a valid account");
198             return null;
199         }
200     }
201
202     // Report bank activity.
203     // For each BankAccount, print the customer id (name or number),
204     // account balance and the number of transactions.
205     // Then print Bank totals.
206
207     private void report()
208     {
209         atm.println( "\nSummaries of individual accounts:" );
210         atm.println( "account  balance   transaction count" );
211         for (int i = 0; i < NUM_ACCOUNTS; i++ ) {             ///
212             atm.println(i + "\t" + accountList[i].getBalance() +     ///
213                         "\t" + accountList[i].getTransactionCount());///
214         }
215
216         atm.println( "\nBank totals");
217         atm.println( "open accounts: " + getNumberOfAccounts() );
218         atm.println( "cash on hand: $" + getBalance());
219         atm.println( "transactions:  " + getTransactionCount());
220         atm.println();
221     }
222
223
224     // Welcome the user to the bank and instruct her on
```

```
225      //  her options.
226
227      private void instructUser()
228      {
229          atm.println( "Welcome to " + bankName );
230          atm.println( "Open some accounts and work with them." );
231          help( BANKER_COMMANDS );
232      }
233
234      // Display a help string.
235
236      private void help( String helpString )
237      {
238          atm.println( helpString );
239          atm.println();
240      }
241
242      /**
243       * Increment bank balance by given amount.
244       *
245       * @param amount the amount increment.
246       */
247
248      public void incrementBalance(int amount)
249      {
250          balance += amount;
251      }
252
253      /**
254       * Increment by one the count of transactions,
255       * for this bank.
256       */
257
258      public void countTransaction()
259      {
260          transactionCount++;
261      }
262
263      /**
264       * Get the number of transactions performed by this bank.
265       *
266       * @return number of transactions performed.
267       */
268
269      public int getTransactionCount( )
270      {
271          return transactionCount ;
272      }
273
274      /**
275       * Get the current bank balance.
276       *
277       * @return current bank balance.
278       */
279
280      public int getBalance()
```



```
281      {
282          return balance;
283      }
284
285      /**
286       * Get the current number of open accounts.
287       *
288       * @return number of open accounts.
289       */
290
291      public int getNumberOfAccounts()
292      {
293          return NUM_ACCOUNTS; /// needs changing ...
294      }
295
296      /**
297       * Run the simulation by creating and then visiting a new Bank.
298       * <p>
299       * A -e argument causes the input to be echoed.
300       * This can be useful for executing the program against
301       * a test script, e.g.,
302       * <pre>
303       *   java Bank -e < Bank.in
304       * </pre>
305       *
306       * @param args the command line arguments:
307       *         <pre>
308       *         -e echo input.
309       *         bankName any other command line argument.
310       *         </pre>
311       */
312
313      public static void main( String[] args )
314      {
315          // parse the command line arguments for the echo
316          // flag and the name of the bank
317
318          boolean echo    = false;        // default does not echo
319          String bankName = "River Bank"; // default bank name
320
321          for (int i = 0; i < args.length; i++ ) {
322              if (args[i].equals("-e")) {
323                  echo = true;
324              }
325              else {
326                  bankName = args[i];
327              }
328          }
329          Bank aBank = new Bank( bankName, new Terminal(echo) );
330          aBank.visit();
331      }
332  }
```