```
// joi/7/jfiles/JFile.java
//
//
// Copyright 2003 Bill Campbell and Ethan Bolker

import java.util.Date;
import java.io.File;

/**
 * A JFile object models a file in a hierarchical file system.
 * <p>
 * Extend this abstract class to create particular kinds of JFiles,
 * e.g.:<br>
 * Directory  -
 *    a JFile that maintains a list of the files it contains.<br>
 * TextFile  -
 *    a JFile containing text you might want to read.<br>
 *
 * @see Directory
 * @see TextFile
 *
 * @version 7
 */

public abstract class JFile
{
    /**
     * The separator used in pathnames.
     */

    public static final String separator = File.separator;

    private String    name;       // a JFile knows its name
    private User      owner;      // the owner of this file
    private Date      createDate; // when this file was created
    private Date      modDate;    // when this file was last modified
    private Directory parent;     // the Directory containing this file

    /**
     * Construct a new JFile, set owner, parent, creation and
     * modification dates. Add this to parent (unless this is the
     * root Directory).
     *
     * @param name     the name for this file (in its parent directory).
     * @param creator  the owner of this new file.
     * @param parent   the Directory in which this file lives.
     */

    protected JFile( String name, User creator, Directory parent )
    {
        this.name   = name;
        this.owner  = creator;
        this.parent = parent;
        if (parent != null) {
            parent.addJFile( name, this );
        }
```



```
        createDate  = modDate = new Date(); // set dates to now
    }

    /**
     * The name of the file.
     *
     * @return the file's name.
     */

    public String getName()
    {
        return name;
    }

    /**
     * The full path to this file.
     *
     * @return the path name.
     */

    public String getPathName()
    {
        if (this.isRoot()) {
            return separator;
        }
        if (parent.isRoot()) {
            return separator + getName();
        }
        return parent.getPathName() + separator + getName();
    }

    /**
     * The size of the JFile
     * (as defined by the child class)..
     *
     * @return the size.
     */

    public abstract int getSize();

    /**
     * Suffix used for printing file names
     * (as defined by the child class).
     *
     * @return the file's suffix.
     */

    public abstract String getSuffix();

    /**
     * Set the owner for this file.
     *
     * @param owner the new owner.
     */

    public void setOwner( User owner )
```

```
113      {
114          this.owner = owner;
115      }
116
117      /**
118       * The file's owner.
119       *
120       * @return the owner of the file.
121       */
122
123      public User getOwner()
124      {
125          return owner;
126      }
127
128      /**
129       * The date and time of the file's creation.
130       *
131       * @return the file's creation date and time.
132       */
133
134      public String getCreateDate()
135      {
136          return createDate.toString();
137      }
138
139      /**
140       * Set the modification date to "now".
141       */
142
143      protected void setModDate()
144      {
145          modDate = new Date();
146      }
147
148      /**
149       * The date and time of the file's last modification.
150       *
151       * @return the date and time of the file's last modification.
152       */
153
154      public String getModDate()
155      {
156          return modDate.toString();
157      }
158
159      /**
160       * The Directory containing this file.
161       *
162       * @return the parent directory.
163       */
164
165      public Directory getParent()
166      {
167          return parent;
168      }
```



```
169
170      /**
171       * A JFile whose parent is null is defined to be the root
172       * (of a tree).
173       *
174       * @return true when this JFile is the root.
175       */
176
177      public boolean isRoot()
178      {
179          return (parent == null);
180      }
181
182      /**
183       * How a JFile represents itself as a String.
184       * That is,
185       * <pre>
186       *    owner   size    modDate    name+suffix
187       * </pre>
188       *
189       * @return the String representation.
190       */
191
192      public String toString()
193      {
194          return getOwner() + "\t" +
195              getSize()  + "\t" +
196              getModDate()  + "\t" +
197              getName() + getSuffix();
198      }
199  }
```